For Residential and Commercial Applications

Job Name	Engineer / Architect	
Job Location	Wholesaler	
Submittal Date	Contractor	

129 Series Hose Barb to Male Iron Pipe 90 Degree Elbow

Use: For use with plastic or rubber tubing. Installation requires a hose clamp.

Design Features:

- Forged brass body
- Manufactured with dryseal pipe threads
- Available in a broad range of sizes

Operating Specifications:

Temperature: -40° to 160°F **Working Pressure:** 150 PSI maximum

Body Brass

Part Listing:

•	
129-4-2	1/4" hose barb x 1/8" MIP
129-4-2 B	1/4" hose barb x 1/8" MIP, bulk
129-4-4	1/4" hose barb x 1/4" MIP
129-4-4 B	1/4" hose barb x 1/4" MIP, bulk
129-5-2	5/16" hose barb x 1/8" MIP
129-5-2 B	5/16" hose barb x 1/8" MIP, bulk
129-5-4	5/16" hose barb x 1/4" MIP
129-5-4 B	5/16" hose barb x 1/4" MIP, bulk
129-5-6	5/16" hose barb x 3/8" MIP
129-6-2	3/8" hose barb x 1/8" MIP
129-6-2 B	3/8" hose barb x 1/8" MIP, bulk
129-6-4	3/8" hose barb x 1/4" MIP
129-6-4 B	3/8" hose barb x 1/4" MIP, bulk
129-6-6	3/8" hose barb x 3/8" MIP
129-6-6 B	3/8" hose barb x 3/8" MIP, bulk
129-6-8 B	3/8" hose barb x 1/2" MIP
129-8-4	1/2" hose barb x 1/4" MIP
129-8-4 B	1/2" hose barb x 1/4" MIP, bulk
129-8-6	1/2" hose barb x 3/8" MIP
129-8-6 B	1/2" hose barb x 3/8" MIP, bulk
129-8-8	1/2" hose barb x 1/2" MIP
129-8-8 B	1/2" hose barb x 1/2" MIP, bulk


This specification and all information contained herein is the confidential and exclusive property of Brasscraft Manufacturing Company and shall not be disclosed to others without the written consent of Brasscraft Mfg. Co. This specification must be returned to Brasscraft Mfg. Co. if requested.



129 Series Hose Barb to Male Iron Pipe 90 Degree Elbow

Part Listing (con't):

129-10-6	5/8" hose barb x 3/8" MIP
129-10-6 B	5/8" hose barb x 3/8" MIP, bulk
129-10-8	5/8" hose barb x 1/2" MIP
129-10-8 B	5/8" hose barb x 1/2" MIP bulk



PART DIMENSIONS (Inches)							
Model	DIA. A	DIA. B	DIM. C	DIM. D	DIM. E		
129-4-2	.281	.156	.63	1.02	.81		
129-4-4	.281	.156	.63	1.03	.88		
129-5-2	.344	.219	.63	1.02	.81		
129-5-4	.344	.219	.63	1.02	.88		
129-5-6	.344	.219	.63	1.09	.94		
129-6-2	.344	.281	.63	1.02	.81		
129-6-4	.422	.281	.63	1.02	.88		
129-6-8	.422	.281	.68	1.09	.94		
129-8-4	.531	.375	.68	1.06	1.00		
129-8-6	.531	.375	.69	1.06	1.09		
129-8-8	.531	.375	.69	1.15	1.12		
129-10-6	.625	.406	.63	.97	.88		
129-10-8	.672	.531	.72	1.13	1.16		

