


Z125

8-3/8 [213] DIAMETER ROOF DRAIN LOW SILHOUETTE DOME

SPECIFICATIONS	SHEET

TAG

Dimensional Data (inches and [mm]) are Subject to Manufacturing Tolerances and Change Without Notice



A Pipe Size In. [mm]	Approx. Wt. Lbs. [kg]	Dome Open Area Sq. In. [cm²]
2, 3, 4 [51, 76, 102]	14 [6]	43 [277]

ENGINEERING SPECIFICATION: ZURN Z125

8-3/8" [213mm] Diameter roof drain, Dura-Coated cast iron body with combination membrane flashing clamp/gravel guard and low silhouette Poly-Dome.

'E' BODY HT. DIM.

OPTIONS (Check/specify appropriate options)

PIPE SIZE

2, 3, 4 [51, 76, 102]
1P Threaded 2-3/4 [70] 4 [102] IP Threaded 3 [76] 2, 3, 4 [51, 76, 102] NH No-Hub 4 [102] 2, 3, 4 [51, 76, 102] NL Neo-Loc 3-13/16 [97] PREFIXES Z D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES A Acid Resistant Epoxy Coated Finish Suffix Similar Simi
4 [102] IP Threaded 3 [76] 2, 3, 4 [51, 76, 102] NH No-Hub 4 [102] 2, 3, 4 [51, 76, 102] NL Neo-Loc 3-13/16 [97] PREFIXES ZA D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES AR Acid Resistant Epoxy Coated Finish SS Stainless Mesh Screen Over Dome C Underdeck Clamp TC Neo-Loc Test Cap Gasket DP Top-Set® Roof Deck Plate TC Neo-Loc Test Cap Gasket VP Vandal Proof Secured Top
2, 3, 4 [51, 76, 102] NH No-Hub 4 [102] 2, 3, 4 [51, 76, 102] NL Neo-Loc 3-13/16 [97] PREFIXES Z D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES AR Acid Resistant Epoxy Coated Finish SS Stainless Mesh Screen Over Dome C Underdeck Clamp TC Neo-Loc Test Cap Gasket DP Top-Set® Roof Deck Plate (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) VP Vandal Proof Secured Top
2, 3, 4 [51, 76, 102] NL Neo-Loc 3-13/16 [97] PREFIXES Z D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES AR Acid Resistant Epoxy Coated FinishSS Stainless Mesh Screen Over DomeC Underdeck ClampTC Neo-Loc Test Cap GasketDP Top-Set® Roof Deck Plate
PREFIXES Z D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES AR Acid Resistant Epoxy Coated FinishSS Stainless Mesh Screen Over Dome C Underdeck ClampTC Neo-Loc Test Cap Gasket DP Top-Set® Roof Deck Plate
Z D.C.C.I. Body with Poly-Dome (4-1/4 [108] Dome Height)* ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXESAR Acid Resistant Epoxy Coated FinishSS Stainless Mesh Screen Over DomeC Underdeck ClampTC Neo-Loc Test Cap GasketDP Top-Set® Roof Deck Plate
ZA D.C.C.I. Body with Aluminum Dome (4-1/4 [108] Dome Height) ZC D.C.C.I. Body with Low Silhouette Cast Iron Dome SUFFIXES AR Acid Resistant Epoxy Coated FinishC Underdeck ClampC Underdeck ClampTC Neo-Loc Test Cap GasketDP Top-Set® Roof Deck Plate (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) (Replaces both the -C and -R) VP Vandal Proof Secured Top
SUFFIXES AR Acid Resistant Epoxy Coated FinishSS Stainless Mesh Screen Over DomeC Underdeck ClampTC Neo-Loc Test Cap GasketDP Top-Set® Roof Deck Plate (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) (Replaces both the -C and -R) -VP Vandal Proof Secured Top
SUFFIXES AR
SUFFIXES AR
 -AR Acid Resistant Epoxy Coated Finish -C Underdeck Clamp -DP Top-Set® Roof Deck Plate (Replaces both the -C and -R) -SS Stainless Mesh Screen Over Dome -TC Neo-Loc Test Cap Gasket (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) -VP Vandal Proof Secured Top
 -AR Acid Resistant Epoxy Coated Finish -C Underdeck Clamp -DP Top-Set® Roof Deck Plate (Replaces both the -C and -R) -SS Stainless Mesh Screen Over Dome -TC Neo-Loc Test Cap Gasket (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) -VP Vandal Proof Secured Top
C Underdeck ClampTC Neo-Loc Test Cap Gasket DP Top-Set® Roof Deck Plate
DP Top-Set® Roof Deck Plate (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only) (Replaces both the -C and -R) -VP Vandal Proof Secured Top
(Replaces both the -C and -R)VP Vandal Proof Secured Top
,
-E Z 15 H Figh Static Extension (Specify Height) -/J vertical Expansion Joint (See Z 190)
EB Top-Set® Adjustable Extension Assembly84 Stainless Steel Perforated Gravel Guard
FG Flush Grate (Replaces Dome Strainer)85 Stainless Steel Perforated Extension
G Galvanized Cast Iron89 2 [51] High External Water Dam
R Roof Sump Receiver90 90° Threaded Side Outlet Body
SC Secondary Clamping Collar (2, 3, 4 [51, 76, 102]) (Previously Z126)
* Regularly furnished unless otherwise specified.

(Specify size/type) OUTLET

Zurn Industries, LLC | Specification Drainage Operation

1801 Pittsburgh Avenue, Erie, PA U.S.A. 16502 · Ph. 855-663-9876, Fax 814-454-7929

In Canada | Zurn Industries Limited

3544 Nashua Drive, Mississauga, Ontario L4V 1L2 · Ph. 905-405-8272, Fax 905-405-1292

Rev. M

Date: 09/25/2017 C.N. No. 137801

Prod. | Dwg. No. Z125